

Fully-Synthetic Multi-Grade Petrol Engine Oil

SBK SAE 0W-16 API SP is a premium fully synthetic passenger car motor oil formulated with advanced synthetic base oils and state-of-the-art additive technology. It is designed to provide exceptional engine protection, improved fuel economy, excellent low-temperature performance, and enhanced protection against Low-Speed Pre-Ignition (LSPI) in modern gasoline and hybrid engines requiring SAE 0W-16 viscosity grade oils. It meets/exceeds the latest API SP and ILSAC GF-6B performance requirements

PERFORMANCE, FEATURES & BENEFITS

- Outstanding fuel economy performance
- Excellent cold-start protection
- Superior wear protection and engine cleanliness
- Enhanced protection against LSPI
- Excellent oxidation and thermal stability
- Reduced sludge and deposit formation
- Extended engine life
- Protects catalytic converters and emission control systems.

MAIN APPLICATIONS

- Modern gasoline passenger cars
- Hybrid electric vehicles (HEV/PHEV)
- Turbocharged gasoline engines
- Vehicles requiring SAE 0W-16 viscosity
- Suitable for many OEMs where 0W-16 is specified.

SPECIFICATIONS & RECOMMENDATIONS

- API SP Resource Conserving
- ILSAC GF-6B

PRODUCT SPECIFICATIONS

TEST PARAMETER	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear and bright
KV @ 40°C	ASTM D445	37
KV @ 100°C	ASTM D445	7.2
Viscosity Index	ASTM D2270	162
Density @ 15°C	ASTM D4052	0.8376
Flash Point	ASTM D92	≥ 210
Pour Point	ASTM D97	-45
CCS @ -35°C	ASTM D5293	5400
TBN	ASTM D2896	8.4