

UNIVERSAL TRACTOR TRANSMISSION OIL UTTO SAE 10W30

Product Data Sheet

SBK UTTO 10W30 is a high-performance Universal Tractor Transmission Oil specially formulated with premium base oils and advanced additive technology to provide excellent lubrication, wear protection, smooth transmission operation, and reliable hydraulic performance in agricultural and off-highway equipment. It is designed for use in transmissions, hydraulic systems, wet brakes, final drives, and power take-off systems requiring UTTO type lubricants. SBK UTTO 10W30 is a high-performance Universal Tractor Transmission Oil specially formulated with premium base oils and advanced additive technology to provide excellent lubrication, wear protection, smooth transmission operation, and reliable hydraulic performance in agricultural and off-highway equipment. It is designed for use in transmissions, hydraulic systems, wet brakes, final drives, and power take-off systems requiring UTTO type lubricants.

PERFORMANCE, FEATURES & BENEFITS

- Excellent anti-wear protection
- Smooth wet brake and clutch performance
- Reduces brake chatter and noise
- Good oxidation and thermal stability
- Protects against rust and corrosion
- Excellent hydraulic response
- Good low-temperature fluidity
- Extends equipment service life

MAIN APPLICATIONS

- Agricultural tractors
- Hydraulic systems
- Power shift transmissions
- Wet brake and wet clutch systems
- Final drives and differentials
- Off-highway and construction equipment
- Farm machinery requiring UTTO 10W30 fluid

SPECIFICATIONS & RECOMMENDATIONS

- John Deere J20C
- Massey Ferguson CMS M1145 / M1143
- CNH MAT 3525 / 3505
- Ford M2C134-D
- Caterpillar TO-2
- Allison C-4
- API GL-4
- Denison HF-0 / HF-1 / HF-2

UNIVERSAL TRACTOR TRANSMISSION OIL UTTO SAE 10W30

Product Data Sheet

PRODUCT SPECIFICATIONS

TEST PARAMETER	TEST METHOD	TYPICAL VALUE
Appearance	Visual	Clear and bright
KV @ 40°C	ASTM D445	58
KV @ 10°C	ASTM D445	9.8
Viscosity Index	ASTM D2270	155
Density @ 15°C	ASTM D4052	0.8634
Flash Point	ASTM D97	≥ 210
Pour Point	ASTM D97	-39

* Note: Typical value; may vary slightly. Please contact your SBK representative for the current batch COA (Certificate Of Analysis)